


fiamma 

SINCE 1977


C O M P A S S
M U L T I B O I L E R



C O M P A S S

COMPASS

MULTI BOILER




MultiBoiler

Independent boilers for steam and coffee. PID temperature control in 3 areas: steam boiler, coffee boilers and groups.



Touchscreen display

Easy real time control, management and monitoring of doses, temperatures, counters – and much more!



PHS

Water pre-heating system: by passing through the steam boiler the water is pre-heated, before it arrives at the coffee boiler, ensuring thermal stability and better performance.



Extraction and shot timers monitoring

Monitor the quality of extraction in the display and with the shot timers, in each group.



Pre-infusion

Programmable pre-infusion time.


C O M P A S S

M U L T I B O I L E R



360° steam wands

Steam at any angle, with handle blocking, for a more agile use.




Cool touch wands

Ergonomic wands, with thermal insulation, so the barista can handle the wands at any time, without burning.



LED Lighting

A look both functional and elegant.



Portioned & Mixed Hot Water

Programmable hot water mix, with temperature control.



Tall Cups or Low Cups

Choose between tall cups or low cups, with retractable stainless steel supports, for espresso coffee.

fiamma

SINCE 1977



hello@fiamma.pt



C O M P A S S M U L T I B O I L E R

	COMPASS 2 MB	COMPASS 3 MB
Boiler technology	MULTIBOILER	
Steam boiler capacity	10.5 l	12 l
Coffee boiler capacity/ power	2 x 0.5 l (2 x 1.5 kW)	3 x 0.5 l (3 x 1.5 kW)
Hot water	1 (portioned & mixed)	1 (portioned & mixed)
Steam wands	2 Cool touch 360° lever tap	2 Cool touch 360° lever tap
Overall power	3.7 ~ 6.7 kW	4.3 ~ 8.8 kW
Power supply	~220-240 V/ 400 V ~2 N	~220-240 V/ 400 V ~2 N
Dimensions	750x600x590 mm	960x600x590 mm
Weight	61 kg	73 kg

C O M P A S S

MKT0122