



- Suitable for residential and commercial water softening applications, as coffee machines, dishwashers, microwave ovens.
- Tank in 304 Stainless Steel.
- They work with mains water pressure.
- They are supplied with and must be operated only with resin approved for drinking water contact use.
- For regeneration use only Sodium Chloride (NaCl) = coarse cooking salt.
- All the constituent materials comply with the requirements of Italian Ministerial Decree 174 dated 04-04-2004, materials in contact with drinking water.

Technical characteristics:

Nominal Flow Rate at 4 bar = 1.000 l/h
 Operating Water Pressure Range: 1 ÷ 4 bar
 Feed Water Temperature Range: 4 ÷ 25°C
 Room Temperature Range: 4 ÷ 35° C
 Connections: 3/4" G - 3/8" G

Ref.	Model	Height (mm)	Diameter (mm)	Softener Weight (kg)	Resin Volume (litres)	Salt/Regeneration (kg)	Litres of water softened based on hardness		
							20°f 200 ppm CaCO3	30°f 300 ppm CaCO3	40°f 400 ppm CaCO3
ADD06	06	360	180	5	3,6	0,5	1000	660	500
ADD08	08	440	180	7	5	0,9	1400	920	700
ADD12	12	560	180	9	8	1,5	2200	1500	1100
ADD16	16	730	180	12	11	2	3000	2000	1500
ADD20	20	730	200	19	14	2,5	3850	2500	1925